

# HAND DRYERS




## ML\_ECLIPSE05\_SS

Eclipse Slimline Automatic Operation Hand Dryer in Satin Stainless Steel

### Specification

Material	1.2mm #304 Satin Stainless Steel
Finish	Satin Stainless Steel
Motor	500W, 16,000-29,000 r.p.m, adjustable brush type, dual ball bearings
Features	Touch-free Patented high-flow dual air outlets
Warranty	5-Year Warranty (3 Years Parts and Labour+ 2 Years Parts only)
Power Use	220-240 Volts, 50Hz
Dimensions	220mmW x 287.9mmH x 100mmD
Operating Sound Level	72db (+-3)@1M db
Motor Speed (Max Settings)	29,000 RPM
Motor Speed (Min Settings)	16,000 RPM
Motor Speed Notes	250-500W Brush Type, Dual Ball Bearings, 95° auto reset overload
Air Speed (Max Settings)	115m/s ==257MPH
Air Speed (Min Settings)	95m/s ==212MPH
Heater Element Power	325-500 Watts, adjustable
Motor Cut-Off Time	60-second power cut off, auto reset
Rated Power (Max Settings)	1000 Watts
Rated Power (Min Settings)	575 Watts
Rated Power Notes	Motor 250-500W, Heating Element 325-500W
Energy Per Day (Min Setting)	2.4 Watt-hours (Wh)
Energy Per Day (Max Setting)	4.17 Watt-hours (Wh)
Sensor Type	Infrared Automatic - 152mm +/- 20mm present blue LED indicates operation/range
Drying Time	Less than 15 seconds
Carbon Dioxide Emission	305g Only
IP Rating	IP24
DP Rating	IPX 1
Heater Element	325-500W
Heater	Auto resetting thermostat turns unit off at 85°C
Warm Air	Speed: 95m/s - 115m/s (Adjustable). Temp: Ambient +30°
Protection	60-sec power cut off, auto reset
Timing	2 sec delay turn off after the last read
Case Security	2 SS theft-resistant hex drive screws (hex key supplied)
Net Weight	4.2kg



Also Available

[ML ECLIPSE DESIGNER](#): Designer Black

[ML ECLIPSE01\\_WHT](#): Stainless Steel

For Metlam Australia's extensive Hand Dryer Range Click on the link [here](#)

Note

\* The unit can be hard-wired by an electrician or used with the cord and plug provided

\*This unit is accessible compliant when installed in accordance with AS1428.1. guidelines.

\* Hardwire - 80mm from the connection point to the wall.

\* Cord and plug - 80mm from the connection point to the bottom of the unit.

For installation instructions download the Metlam Australia App



Safety Approvals - [Click here to download more information](#)



Green Certificates

**WEEE RoHS**



## Downloads & Resources

Care & Maintenance

Installation instructions

Mounting template

Revit

Promotions

Associated Videos

Stainless Steel Cleaning & Maintenance

Discover the Difference

Trouble Shooting your Metlam Australia Hand Dryer

How to install a Metlam Australia Eclipse Hand Dryer

The photographs and line drawings of the products presented above are representational only. Metlam Australia Pty Ltd reserves the right to, and from time to time, make changes and improvements in design and dimensions.